B.356-66(Rev 67) **STONE & WEBSTER ENGINEERING LIMITED** Sheet 1 of 4

STEAM TURBINE SPECIFICATION

Client BP CHEMICALS (U.K.) LTD. P.O. No.

Project or Plant No. 2 ETHYLENE Location BAGLAN BAY Job No. 6631

Service CRACKED GAS COMPRESSOR STAGES 1 AND 2 DRIVER Indoors/Outdoors

Size & Type K-1100-2 Manufacturer SIEMENS Duty CONTINUOUS

Gear/Direct Drive Mounted By OTHERS No. of Units TWO

STEAM (PRESSURES ARE GAUGE)

Inlet	NORMAL	MAXIMUM	DESIGN	Extraction	NORMAL	MAXIMUM	DESIGN
Pressure lbf/in²: Kgf/cm²	190	210	300	Pressure lbf/in²: Kgf/cm²			
Temperature °F: °C	480	480	480	Temperature °F: °C			
Flow lb/h: Kg/h E/hr	37.1	43.3		Flow lb/h: Kg/h			
Test Press lbf/in² SECTION 1	632			Exhaust Press: lbf/in² Kgf/cm²	1.7 ABS.		
SECT 2-4	397			Exhaust Temp. °F : °C			
				Casing Dsn Press lbf/in² : Kgf/cm²			

COOLING WATER

	NORMAL	MAXIMUM	DESIGN		
Supply Press lbf/in²: Kgf/cm²	65		150	Max. Allow Press Drop lbf/in2: Kgf/cm²	20
Supply Temp °F : °C	80			Design Press Water Jacket :	150
Return Temp °F : °C	120			Test " " " " : "	

DRIVEN EQUIPMENT

Description	CENTRIFUGAL COMPRESSOR	Rotation Facing Coupling	CCW
Speed rev/min: (MAX)	4560	Make & Type of Coupling	
Normal BHP AND SPEED	8110/4230	Starting Torque ftlb: Mkg	
Maximum BHP	9130	Critical Speed rev/min:	1st 2nd

TURBINE

No. of Stages	1 + 21	Rated BHP Hand Valves Shut	NO HAND VALVES
Casing Split	HORIZONTAL	Max. BHP Hand Valves Open	-
Shaft Arrangement	HORIZONTAL	No. of VALVES open at Full Load	5
Steam Chest Material	CS GSC 25	No. of Auxiliary Hand Valves	-
Exhaust Casing Material	CI	Rated Speed rev/min:	4560
Blades or Buckets Material	X22 Cr Mo V12.1	Speed Change :	3807-4560
Shaft Material	34 Cr Mo 4	Steam Consumption KG/KW/HR :-	6.13
Sole Plate	CARBON STEEL	At Rated BHP & rev/min:	8110/4230
Cooling Water Piping Material	C.S	At 75% BHP & Rated :	
Lube Oil Piping	S.S.	Rotation	Same as Line 23
Bearings, Type JOURNAL	MULTI WEDGE	Inlet Size & Rating	8"
Speed Governor, Type HYDRAULIC	SIEMENS	Exhaust Size & Rating	44" DUAL
Hand Speed Changer	YES.	Cooling Water In & Out	
Emergency Governor Type BOLT	YES/NO SET	Lube Oil in & out TURB. BEARING	45/55°C
ATMOS. RELIEF Valve lbf/in² Kgf/cm²	SET APPROX 15.6 Abs	Insulation Type	ASBESTOS MATS
Steam Strainer	YES	Steel Lagging	YES
Inlet Valve	YES/NO	Recommended Grade of oil:-	TO DIN 51515
Outlet Valve	YES/NO	Bearings	3.0-4.5 E at 50°C
Type of Lubrication	FORCED	Governor System	
Type of Oil Cooler	-	Total Oil Quantities for Start up:	24.7 m³/hr
Operating Press Oil Cooler lbf/in² : Kgf/cm²	-	Quantity Cooling Water:-	
Design Press Oil Cooler " : "	-	Bearings gpm: m³/h	
Characteristic Curve No.		Oil Cooler gpm: m³/h	
Turbine Critical Speed rev/min:	1st 6500 2nd	Approx. Weight Unit Lbs: Kg	12,100
Design Code Turbine	API 615 SP. PURP.	Approx Weight Rotor : Kg	1550
Design Code Cooler		Weight of Top half casing Lbs: Kg	5[illegible]

REMARKS * MAX. EFFIC. DUTY WITH STEAM AT 200PSIG ; ** MCR WITH STEAM AT [illegible]

Ref. Drgs.

Ref. Specs.

CERTIFIED [signature] ACCOUNT F

EQUIPMENT No. H-CT-1A AND B

B.M. No. 6631 R-2

SPEC. No. 6631-RT-1

ISSUE	DATE	DESCRIPTION OF ISSUE	CH'K	APP.
TT	15/3/71	LINES 14 & 15 TEST PRESS ADDED	ANS	VD
TTT	14/7/70	AMENDED	[illegible]	[illegible]
TT	15/[illegible]	CERTIFIED	JA	VD
I	17.12.69	ENQUIRY		